

TOP VIEW




LABEL:

MADE BY AMGIS LLC USA
 INDUCTOR P/N IND-10565A
 L= 1.2 mH I= 7.2A
 DATE CODE-S/N

RELEASE HISTORY			
REL.	DESCRIPTION	DATE	APPROVED
000	INITIAL RELEASE	06/05/2014	JJ

SCHEMATIC



WIND BACK & FORTH IN 5 LAYERS.

NOTES:

1. HEADER: LODESTONE PACIFIC VTM254-4 (WITH 4 PINS #16 AWG)
2. CORE MICROMETALS T200-8/90
3. MAGNET WIRE 16 HPTZ.
4. EPOXY JB WELD OR APPROVED EQUIVALENT.
5. SOLDER SN96

ELECTRICAL

1. INDUCTANCE @ 250 mV, 15 KHz:
(1-2)= 1.8 mH ± 10%
2. DCR:
(1-2)= 175mΩ REF



<p>AMGIS LLC, INC PROPRIETARY AND CONFIDENTIAL THIS DRAWING IS THE PROPERTY OF AMGIS LLC, INC. IT IS LOANED WITH THE UNDERSTANDING THAT IT MAY NOT BE REPRODUCED NOR MAY THE INFORMATION CONTAINED HEREIN BE USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN CONSENT FROM AMGIS LLC, INC.</p>	NAME	DATE	TITLE:		
	DRAWN	DF	06/05/2014	INDUCTOR	
	APPROVED	JJ	06/05/2014		
	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			DWG. NO	REL
TOLERANCES: FRACTIONS: ± 1/64 ONE PLACE DECIMAL: ± .050 TWO PLACE DECIMAL: ± .010 THREE PLACE DECIMAL: ± .005			IND-10565A	000	
DO NOT SCALE DRAWING			SCALE: NONE	WEIGHT: .6 LBS	SHEET 1 OF 1